



WHITE SPIRIT

Issue 4 – November 2008

Description: Cromar White Spirit is a hydrocarbon solvent suitable for general cleaning purposes and brush cleaning.

Packaging: 750ml, 2, 4 and 25 Litre.

Technical Data:

Property	Minimum	Maximum	Typical	Test Method
Density 15°C kg/l	0.770		0.785	ASTM D 1298
Colour (Saybolt)	+25		+25	ASTM D 156
Distillation (°C) IBP	150		156	ASTM D 86
DP		200	198	
Flashpoint °C	38		41*	IP 170
Aromatic Content Volume (%)		25	17	ASTM D 1319
Copper Corrosion 3 hours as 100°C			1	ASTM D 130

Conforms in all aspects with BS 245: 1976, Type A.

* If Flashpoint is critical, figure of current stock should be ascertained at time of placing order.

Health & Safety: Please refer to Health and Safety Data Sheet on White Spirit.

Further Information: In the event of further queries or problems concerning the use of this product, please contact the address below:-

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar's products' are available for sale in accordance with Cromar's Standard Terms and Conditions of Sale, which are available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our Representatives, Agents, or Distributors, as the conditions of use, and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.

Unit 3, The Maltings Industrial Estate
Doncaster Road, Whitley Bridge
North Yorkshire DN14 0HH
Tel: 01977 663133 Fax: 01977 662186
info@cromar.uk.com www.cromar.uk.com



CROMAR
BUILDING PRODUCTS LIMITED