

FAQ's DRY SEAL™ MP

Repair Care Ltd Unit 19, Darwell Park Mica Close, Amington, Tamworth Staffordshire, B77 4DR T: 01827 302 517 E-mail: salesuk@repair-care.com



Frequently Asked Questions - DRY SEAL[™] MP

Please refer to the <u>product pages</u> and product <u>data sheets</u>, or <u>contact us</u> for further information.

- 1. How quickly can I paint DRY SEAL[™] MP?
- 2. Can I use DRY SEAL[™] MP on metal windows frames?
- 3. Can I use DRY SEAL[™] MP around my shower/toilet?
- 4. What happens if it rains shortly after application of DRY SEAL™ MP?
- 5. Is DRY SEAL[™] MP safe with double glazed units or specialist glass?
- 6. Is DRY SEAL[™] MP approved by conservation surveyors and architects?
- 7. What is the best technique for getting a smooth finish?
- 8. My glazing supplier says I must use non-silicone/non-butile, can I use DRY SEAL™ MP?
- 9. How can I remove smears of dried DRY SEAL[™] MP from glass?
- 10. Is DRY SEAL[™] MP guaranteed?
- 11. What happens if DRY SEAL[™] MP goes over its expiry date?
- 12. DRY SEAL[™] MP is brilliant white can I leave it unpainted?

1. How quickly can I paint DRY SEAL[™] MP?

We recommend a minimum of 2 hours before painting.

2. Can I use DRY SEAL[™] MP on metal windows frames?

Yes. Please see the guidance notes on the product data sheet.

3. Can I use DRY SEAL[™] MP around my shower/toilet?

No, it is not suitable for this type of application.

4. What happens if it rains shortly after application of DRY SEAL[™] MP?

DRY SEAL[™] MP should only be applied in dry weather but will not be affected by rain once it is applied.

5. Is DRY SEAL[™] MP safe with double glazed units or specialist glass?

DRY SEAL[™] MP has been tested and is compatible with a wide variety of glazing including acoustic, laminated, sealed double-glazing, Slimlite double glazing, plate, solar reflective and self-cleaning glass. It can also be used with polycarbonate glazing.

TOTAL JOINERY REPAIR SOLUTIONS



6. Is DRY SEAL[™] MP approved by conservation surveyors and architects?

Usually yes, but please check before applying.

7. What is the best technique for getting a smooth finish?

Please refer to the guidance notes and instruction video on the product page.

8. My glazing supplier says I must use non-silicone/non-butile, can I use DRY SEAL™ MP?

Yes, DRY SEAL[™] MP is a specific modified silane terminated polymer.

9. How can I remove smears of dried DRY SEAL[™] MP from glass?

DRY SEAL[™] MP should be applied carefully, without over filling the rebate. Excess is best removed from the glass with a sharp blade when it is cured.

10. Is DRY SEAL[™] MP guaranteed?

Yes, our products are <u>guaranteed</u> for 10 years, subject to conditions.

11. What happens if DRY SEAL[™] MP goes over its expiry date?

We do not recommend you use any product after its expiry date.

12. DRY SEAL[™] MP is brilliant white – can I leave it unpainted?

DRY SEAL[™] MP has UV resistance so can be left unpainted but painting will help protect against surface pollution.