



Timber Inspired, Quality Driven

# J53 External Grade D3 polyvinyl acetate adhesive

## Safety Data Sheet

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

Trade name - Xylo J53 D3 PVA

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / preparation: Industrial

Binder for: Adhesives , coating

All other areas of application to be agreed with the Application Engineering/ Technical Marketing Department of the manufacturer.

#### 1.3 Details of the supplier of the safety data sheet

##### Distributor:

Toolfix Joinery & Construction Supplies Ltd

Pentagon House

Neward Road

Peterborough, PE1 5UA

T: +44 (0)1733 347348

E: enquiries@toolfixservices.com

#### 1.4 Emergency telephone number: +44 (0)1733 347348

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008:

Not a hazardous substance or mixture.

#### 2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008:

No labeling according to GHS required.

Special labelling instructions:

Safety data sheet available on request. Contains chloromethylisothiazolinone and methylisothiazolinone (3:1). May produce an allergic reaction.

#### 2.3 Other hazards

N0 data available

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

not applicable

#### 3.2 Mixtures

##### 3.2.1 Chemical characteristics

Polyvinyl acetate (dispersion in water)



Timber Inspired, Quality Driven

# J53 External Grade D3 polyvinyl acetate adhesive

## Safety Data Sheet

### 3.2.2 Hazardous ingredients

Type	CAS No.	EC-No.	Material	Content %	Classification according to Regulation (EC) No. 1272/2008*	Comment
		REACH no.				
INHA	108-32-7	203-572-1	Propylene carbonate	<5	Eye Irrit. 2; H319	[1]
		01-2119537232-48				

Type: INHA: ingredient, VERU: impurity

[1] = Hazardous or environmentally harmful substance; [2] = substance with a Community workplace exposure limit; [3] = PBT substance; [4] = vPvB substance

\*Classification codes are explained in section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General information:

Under ordinary workplace conditions: No special measures required.

##### After contact with the eyes:

Rinse immediately with plenty of water. Seek medical advice in case of continuous irritation.

##### After contact with the skin:

**Wash with plenty of water or water and soap. Seek medical advice in case of continuous irritation.**

##### After inhalation:

No special measures required.

##### After swallowing:

In cases of sickness seek medical advice (show label if possible).

#### 4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Due to its physical properties, may cause mechanical irritation. Product may agglutinate in the gastro-intestinal tract. Medical assistance should be sought. Depending on the symptoms, invasive measures may be necessary. Further toxicology information in section 11 must be observed.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media:

not applicable.

##### Extinguishing media which must not be used for safety reasons:

not applicable.

#### 5.2 Special hazards arising from the substance or mixture

At low oxygen level: acetic acid.

#### 5.3 Advice for firefighters

##### Special protective equipment for fire fighting:

Use respiratory protection independent of recirculated air.

##### General information:

Product does not burn. Use extinguishing measures appropriate to the source of the fire. Dried up material is combustible.



Timber Inspired, Quality Driven

# J53 External Grade D3 polyvinyl acetate adhesive

## Safety Data Sheet

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment (see section 8). If material is released indicate risk of slipping.

#### 6.2 Environmental precautions

Prevent material from entering sewers or surface waters. Contain any fluid that runs out using suitable material (e.g. earth).

#### 6.3 Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. For small amounts: Absorb with a liquid binding material such as diatomaceous earth and dispose of according to local/state/federal regulations. Contain larger amounts and pump up into suitable containers. Clean up with plenty of water. Dispose of cleansing water in accordance with local/state/federal regulations.

#### 6.4 Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### General information:

No special protective measures required.

##### Precautions for safe handling:

Spilled substance increases risk of slipping.

##### Precautions against fire and explosion:

No special precautions against fire and explosion required.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Conditions for storage rooms and vessels:

Protect against frost.

##### Advice for storage of incompatible materials:

not applicable.

##### Further information for storage:

not applicable.

##### Minimum temperature allowed during storage and transportation: 0 °C

#### 7.3 Specific end use(s)

No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### 8.2 Exposure controls

##### 8.2.1 Exposure in the work place limited and controlled

##### General protection and hygiene measures:

Do not eat or drink when handling.

##### Personal protection equipment:

##### Respiratory protection

No personal respiratory protective equipment normally required.

##### Eye protection

protective goggles

##### Hand protection

Rubber gloves .

##### Skin protection

not required



Timber Inspired, Quality Driven

# J53 External Grade D3 polyvinyl acetate adhesive

## Safety Data Sheet

### 8.2.2 Exposure to the environment limited and controlled

Prevent material from entering sewers or surface waters.

### 8.3 Further information for system design and engineering measures

No special measures required.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Property:	Value:	Method:
<b>Appearance</b>		
Physical state / form .....	liquid	
Colour.....	white	
<b>Odour</b>		
Odour .....	faint	
<b>Odour limit</b>		
Odour limit :	no data available	
<b>pH-Value</b>		
pH-Value .....	2,5 - 3,5	(DIN/ISO 976)
<b>Melting point/freezing point</b>		
Melting point / melting range .....	approx. 0,00 °C	
<b>Initial boiling point and boiling range</b>		
Boiling point / boiling range .....	approx. 100 °C at 1013 hPa	
<b>Flash point</b>		
Flash point.....	not applicable	
<b>Evaporation rate</b>		
Evaporation rate .....	no data available	
<b>Upper/lower flammability or explosive limits</b>		
Lower explosion limit (LEL) .....	not applicable	
<b>Vapour pressure</b>		
Vapour pressure.....	23 hPa / 20 °C	
<b>Solubility(ies)</b>		
Water solubility / miscibility.....	moderately soluble	
<b>Vapour density</b>		
Relative gas/vapour density .....	No data known	
<b>Relative Density</b>		
Relative Density .....	1,1 (21 °C) (Water / 4 °C = 1,00)	
Density .....	1,1 g/cm <sup>3</sup> (21 °C)	
<b>Partition coefficient: n-octanol/water</b>		
Partition coefficient: n-octanol/water.....	No data known.	
<b>Auto-ignition temperature</b>		
Ignition temperature .....	not applicable	
<b>Viscosity</b>		
Viscosity (dynamic) .....	9000 - 13000 mPa.s at 23 °C	(DIN EN ISO 2555)
<b>Molecular mass</b>		
Molecular mass .....	not applicable	

### 9.2 Other information

No data available.



Timber Inspired, Quality Driven

# J53 External Grade D3 polyvinyl acetate adhesive

## Safety Data Sheet

### SECTION 10: Stability and reactivity

#### 10.1 – 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions

If stored and handled in accordance with standard industrial practices no hazardous reactions are known. Relevant information can possibly be found in other parts of this section.

#### 10.4 Conditions to avoid

none known.

#### 10.5 Incompatible materials

none known.

#### 10.6 Hazardous decomposition products

If stored and handled properly: none known. At increased temperature: acetic acid.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### 11.1.1 Acute toxicity

##### Assessment:

Based on the available data acute toxic effects are not expected after single oral exposure.

##### Product details:

Route of exposure	Result/Effect	Species/Test system	Source
oral	LD50: > 2000 mg/kg	rat	Conclusion by analogy OECD 423

##### 11.1.2 Skin corrosion/irritation

##### Assessment:

Based on the available data a clinically relevant skin irritation hazard is not expected.

##### Product details:

Result/Effect	Species/Test system	Source
not irritating	rabbit	Conclusion by analogy OECD 404

##### 11.1.3 Serious eye damage / eye irritation

##### Assessment:

Based on the available data a clinically relevant eye irritation hazard is not expected.

##### Product details:

Result/Effect	Species/Test system	Source
not irritating	rabbit	Conclusion by analogy OECD 405

##### 11.1.4 Respiratory or skin sensitization

##### Assessment:

Based on the available data a sensitization reaction is not expected from this product.

##### 11.1.5 Germ cell mutagenicity

##### Assessment:

Based on known data a significant mutagenic potential may be excluded.

##### Product details:

Result/Effect	Species/Test system	Source
negative	mutation assay (in vitro) bacterial cells	Conclusion by analogy OECD 471



Timber Inspired, Quality Driven

# J53 External Grade D3 polyvinyl acetate adhesive

## Safety Data Sheet

### 11.1.6 Carcinogenicity

**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

### 11.1.7 Reproductive toxicity

**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

### 11.1.8 Specific target organ toxicity (single exposure)

**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

### 11.1.9 Specific target organ toxicity (repeated exposure)

**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

### 11.1.10 Aspiration hazard

**Assessment:**

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

### 11.1.11 Further toxicological information

No information on damage to health during manufacture and use.

## SECTION 12: Ecological information

### 12.1 Toxicity

**Assessment:**

No expected damaging effects to aquatic organisms. According to current knowledge adverse effects on water purification plants are not expected.

**Product details:**

Result/Effect	Species/Test system	Source
LC50: > 100 mg/l	rainbow trout (Oncorhynchus mykiss) (96 h)	Conclusion by analogy OECD 203
EC50: > 1000 mg/l	Daphnia magna (48 h)	Conclusion by analogy OECD 202
EC10: > 1000 mg/l	sludge (0,5 h)	Conclusion by analogy

### 12.2 Persistence and degradability

**Assessment:**

Polymer component: Not readily biodegradable. Elimination by adsorption to activated sludge. Separation by flocculation is possible.

### 12.3 Bioaccumulative potential

**Assessment:**

No adverse effects expected.

### 12.4 Mobility in soil

**Assessment:**

No adverse effects expected.

### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

none known

### 12.7 Additional information

According to present knowledge no adverse influence to environment expected.



Timber Inspired, Quality Driven

# J53 External Grade D3 polyvinyl acetate adhesive

## Safety Data Sheet

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### 13.1.1 Material

Recommendation:

Dispose of according to regulations by incineration in a special waste incinerator. Small quantities may be disposed of by incineration in an approved facility. Observe local/state/federal regulations.

##### 13.1.2 Uncleaned packaging

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations.

Recommended cleaning agent: water

##### 13.1.3 Waste Disposal Legislation Ref.No.(EC)

It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

### SECTION 14: Transport information

#### 14.1 – 14.4 UN number; UN proper shipping name; Transport hazard class(es); Packing group

##### Road ADR:

Valuation .....: Not regulated for transport

##### Railway RID:

Valuation .....: Not regulated for transport

##### Transport by sea IMDG-Code:

Valuation .....: Not regulated for transport

##### Air transport ICAO-TI/IATA-DGR:

Valuation .....: Not regulated for transport

#### 14.5 Environmental hazards

Hazardous to the environment: no

#### 14.6 Special precautions for user

Relevant information in other sections has to be considered.

#### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk transport in tankers is not intended.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

#### Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances (Seveso III):

Not applicable

Relevant regulations:

SI 2002/1689: CHIP Regulations 2002

SI 2002/2677: COSHH Regulations 2002

SI 1999/3242: Management of Health & Safety at Work Regulations 1999

Health & Safety at Work Act 1974

SI 1993/1643: Environmental Protection Act 1993 & Subsidiary Regulations.

Other national and local measures relating to the workplace, pollution control, environmental protection and waste control.



Timber Inspired, Quality Driven

# J53 External Grade D3 polyvinyl acetate adhesive

## Safety Data Sheet

### Other specifications, restrictions and prohibitions:

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals: Not applicable

### 15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

### 15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

- South Korea (Republic of Korea) ..... : **ECL** (Existing Chemicals List):  
This product is listed in, or complies with, the substance inventory.
- Japan ..... : **ENCS** (Handbook of Existing and New Chemical Substances):  
This product is listed in, or complies with, the substance inventory.
- New Zealand ..... : **NZIoC** (New Zealand Inventory of Chemicals):  
This product is listed in, or complies with, the substance inventory. (For a correct interpretation of the New Zealand status, additional information like GHS classification or Group Standard is required.)
- Australia ..... : **AICS** (Australian Inventory of Chemical Substances):  
This product is listed in, or complies with, the substance inventory.
- Canada ..... : **DSL** (Domestic Substance List):  
This product is listed in, or complies with, the substance inventory.
- Philippines..... : **PICCS** (Philippine Inventory of Chemicals and Chemical Substances):  
This product is listed in, or complies with, the substance inventory.
- United States of America (USA)..... : **TSCA** (Toxic Substance Control Act Chemical Substance Inventory):  
All components of this product are listed as active or are in compliance with the substance inventory.
- Taiwan (Republic of China) ..... : **TCSI** (Taiwan Chemical Substance Inventory):  
This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of this obligation.
- European Economic Area (EEA)..... : **REACH** (Regulation (EC) No 1907/2006):  
General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.





Timber Inspired, Quality Driven

# J53 External Grade D3 polyvinyl acetate adhesive

## Safety Data Sheet

### SECTION 16: Other information

#### 16.1 Material

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

#### 16.2 Further information:

Commas appearing in numerical data denote a decimal point. Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

Explanation of the GHS classification code:

Eye Irrit. 2; H319..... :

Serious eye damage / eye irritation Category 2; Causes serious eye irritation.