



Timber Inspired, Quality Driven

J30 External Grade D4 polyurethane adhesive

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Trade name - Xylo J30 External Grade D4 Polyurethane Adhesive (310ml)

Product Number: AHZ2119

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

Uses advised against No specific uses advised against are

1.3 Details of the supplier of the safety data sheet

Distributor:

Toolfix Joinery & Construction Supplies Ltd

Pentagon House

Neward Road

Peterborough, PE1 5UA

T: +44 (0)1733 347348

E: enquiries@toolfixservices.com

1.4 Emergency telephone number: +44 (0)1733 347348

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Classification (EC 1272/2008)

Physical hazards

Not Classified

Health hazards

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Resp. Sens. 1 - H334 Skin Sens. 1 - H317

Carc. 2 - H351 STOT SE 3 - H335 STOT RE 2 - H373

Environmental hazards

Not Classified

Human health

Contains non-volatile isocyanate. Heating may generate vapours which irritate the respiratory system. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2. Label elements

Pictogram





Timber Inspired, Quality Driven

J30 External Grade D4 polyurethane adhesive

Safety Data Sheet

Signal word

Hazard statements

Danger

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

EUH204 Contains isocyanates. May produce an allergic reaction.

P260 Do not breathe vapour/ spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P281

Use personal protective equipment as required.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P313 Get medical advice/ attention.

P501 Dispose of contents/ container in accordance with national regulations.

RCH004a Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

RCH004b Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

RCH004c This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Precautionary statements

Contains

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE			30-60%
101-68-8	Ec Number: 202-966-0	REACH registration number: 01-2119457014-47-0000	
Classification Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Resp. Sens. 1 - H334 Skin Sens. 1 - H317 Carc. 2 - H351 STOT SE 3 - H335 STOT RE 2 - H373			



Timber Inspired, Quality Driven

J30 External Grade D4 polyurethane adhesive

Safety Data Sheet

2,2'DIMORPHOLINYLDIETHYL ETHER			<1%
CAS number: 6425-39-4	EC number: 229-194-7	REACH registration 01-2119457014-47-0000	
Classification			
Acute Tox. 4 - H332			
Skin Irrit. 2 - H315			
Eye Irrit. 2 - H319			
Resp. Sens. 1 - H334			
Skin Sens. 1 - H317			
Carc. 2 - H351			
STOT SE 3 - H335			
STOT RE 2 - H373			

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Inhalation

Remove affected person from source of contamination.
Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion

DO NOT induce vomiting. Get medical attention immediately.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.

Eye contact

Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.

Protection of first aiders

First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

Irritation of nose, throat and airway. Coughing, chest tightness, feeling of chest pressure.

Ingestion

May cause discomfort if swallowed.

Skin contact

Prolonged skin contact may cause redness and irritation.

Eye contact

Severe irritation, burning and tearing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable

Do not use water jet as an extinguisher, as this will spread the fire.

extinguishing media

5.2. Special hazards arising from the substance or mixture

Specific hazards

Irritating gases or vapours.

Hazardous

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

combustion products



Timber Inspired, Quality Driven

J30 External Grade D4 polyurethane adhesive

Safety Data Sheet

5.3. Advice for firefighters

Protective actions during firefighting

Special protective equipment for firefighters

Containers close to fire should be removed or cooled with water. Do not allow water to contact any leaked material.
Wear chemical protective suit. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid inhalation of vapours and spray/mists. Avoid contact with skin and eyes. Do not use in confined spaces without adequate ventilation and/or respirator. Spraying is permitted only in closed systems, spray cabinets or spray boxes with adequate ventilation. Wash promptly with soap and water if skin becomes contaminated. Preventive industrial medical examinations should be carried out.

Advice on general occupational hygiene

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C.
Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

Long-term exposure limit (8-hour TWA): WEL 0.02 mg/m³(Sen)

Short-term exposure limit (15-minute): WEL 0.07 mg/m³(Sen)

WEL = Workplace Exposure Limit.



Timber Inspired, Quality Driven

J30 External Grade D4 polyurethane adhesive

Safety Data Sheet

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE (CAS: 101-68-8)

Ingredient comments

WEL = Workplace Exposure Limits

DNEL

Workers - Inhalation; Short term systemic effects: 0.1 mg/m³
 Workers - Dermal; Short term local effects: 28.7 mg/cm²
 Workers - Inhalation; Short term local effects: 0.1 mg/m³
 Workers - Inhalation; Long term systemic effects: 0.05 mg/m³
 Workers - Inhalation; Long term local effects: 0.05 mg/m³
 Consumer - Dermal; Short term systemic effects: 25 mg/kg bw/day
 Workers - Dermal; Short term systemic effects: 50 mg/kg bw/day
 Consumer - Oral; Short term systemic effects: 20 mg/kg bw/day
 Consumer - Dermal; Short term local effects: 17.2 mg/cm²
 Consumer - Inhalation; Short term local effects: 0.05 mg/m³
 Consumer - Inhalation; Long term systemic effects: 0.025 mg/m³
 Consumer - Inhalation; Long term local effects: 0.025 mg/m³
 Consumer - Inhalation; Short term systemic effects: 0.05 mg/m³

PNEC

- marine water; 0.1 mg/l
 - STP; 1 mg/l
 - Fresh water; 1 mg/l
 - Soil; 1 mg/kg

2,2'DIMORPHOLINYLDIETHYL ETHER (CAS: 6425-39-4)

DNEL

Workers - Inhalation; Long term systemic effects: 7.28 mg/m³
 Workers - Dermal; Long term systemic effects: 1 mg/kg bw/day
 Consumer - Inhalation; Long term systemic effects: 1.8 mg/m³
 Consumer - Dermal; Long term systemic effects: 0.5 mg/kg bw/day
 Consumer - Oral; Long term systemic effects: 0.5 mg/kg bw/day

PNEC

- Fresh water; 0.1 mg/l
 - Marine water; 0.01 mg/l
 - Intermittent release; 1 mg/l
 - Sediment (Freshwater); 8.2 mg/kg
 - Sediment (Marinewater); 0.82 mg/kg
 - STP; 100 mg/l
 - Soil; 1.58 mg/kg

8.2. Exposure controls Protective equipment





Timber Inspired, Quality Driven

J30 External Grade D4 polyurethane adhesive

Safety Data Sheet

Appropriate engineering

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. This product is not to be used under conditions of poor ventilation. This product must not be handled in a confined space without adequate ventilation. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Eye/face protection

Wear chemical splash goggles.

Hand protection

It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber.

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination. Wear apron or protective clothing in case of contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Wash hands after handling. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: ABEK2-P3

Environmental exposure controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Coloured gel.
Colour	Various colours.
Odour	Musty (mouldy).
Odour threshold	Not available.
pH	Not available.
Melting point	<10°C
Initial boiling point and range	330°C @ mbar
Flash point	>200°C CC (Closed cup).
Evaporation rate	slow
Evaporation factor	Not available.
Flammability (solid, gas)	Not available.
Other flammability	Not available.
Vapour pressure	0.01 Pa @ °C
Vapour density	8.5
Relative density	1.10 @ 20°C
Bulk density	Not available.
Solubility(ies)	Insoluble in water. Hardens in contact with water.
Partition coefficient	Not available.
Auto-ignition temperature	>600°C
Decomposition Temperature	Not available.
Viscosity	Kinematic viscosity > 20.5 mm ² /s.



Timber Inspired, Quality Driven

J30 External Grade D4 polyurethane adhesive

Safety Data Sheet

Explosive properties	Not available.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not available.
Comments	Information given is applicable to the product as supplied.

9.2. Other information

Other information	No information required.
Refractive index	Not available.
Particle size	Not available.
Molecular weight	Not available.
Volatility	Not available.
Saturation concentration	Not available.
Critical temperature	Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	The product will harden into a solid mass in contact with water and moisture.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not applicable. May polymerise.
---	---------------------------------

10.4. Conditions to avoid

Conditions to avoid	Avoid contact with water.
----------------------------	---------------------------

10.5. Incompatible materials

Materials to avoid	Strong acids. Strong alkalis.
---------------------------	-------------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - Inhalation

ATE inhalation (vapours mg/l)	26.83
--------------------------------------	-------

Skin corrosion/irritation

Animal data	Irritating.
--------------------	-------------

Serious eye damage/irritation

Serious eye damage/irritation	Moderately irritating.
--------------------------------------	------------------------

Respiratory sensitisation

Respiratory sensitisation	Sensitising.
----------------------------------	--------------

Carcinogenicity

Carcinogenicity	Suspected carcinogen based on limited evidence.
------------------------	---

Target organ for carcinogenicity

No specific target organs known.

Reproductive toxicity Reproductive toxicity - development

This substance has no evidence of toxicity to reproduction.



Timber Inspired, Quality Driven

J30 External Grade D4 polyurethane adhesive

Safety Data Sheet

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Morphological changes that are potentially reversible but provide clear evidence of marked organ dysfunction.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

Inhalation

Irritating to respiratory system. May cause sensitisation by inhalation.

Ingestion

May cause stomach pain or vomiting.

Skin contact

Irritating to skin. May cause sensitisation by skin contact.

Eye contact

Irritation of eyes and mucous membranes.

Acute and chronic health hazards

May cause sensitisation by skin contact. The product contains small quantities of isocyanate. May cause respiratory allergy. May cause respiratory system irritation. May cause respiratory system irritation. Frequent inhalation of vapours may cause respiratory allergy.

Route of exposure

Inhalation Skin and/or eye contact

Medical symptoms

Irritation of eyes and mucous membranes. Coughing, chest tightness, feeling of chest pressure.

Medical considerations

Chronic respiratory and obstructive airway diseases.

Toxicological information on ingredients.

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

Acute toxicity - oral

Acute toxicity oral 10,000.0
(LD₅₀ mg/kg)

Species Rat

ATE oral (mg/kg) 10,000.0

Acute toxicity - dermal 9,400.0

Acute toxicity dermal
(LD₅₀ mg/kg)

Species Rabbit

ATE dermal (mg/kg) 9,400.0

Acute toxicity - inhalation

Acute toxicity inhalation 0.31
(LC₅₀ vapours mg/l)

Species Rat

ATE inhalation 11.0
(vapours mg/l)

Carcinogenicity

IARC carcinogenicity

IARC Group 3 Not classifiable as to its carcinogenicity to humans.



Timber Inspired, Quality Driven

J30 External Grade D4 polyurethane adhesive

Safety Data Sheet

2,2'DIMORPHOLINYLDIETHYL ETHER

Acute toxicity - oral	
Acute toxicity oral (LD ₅₀ mg/kg)	2,025.0
Species	Rat
Notes (oral LD₅₀)	No information available.
Acute toxicity - dermal	
Acute toxicity dermal (LD ₅₀ mg/kg)	3,038.0
Species	Rabbit
Notes (dermal LD₅₀)	No information available.
Acute toxicity - inhalation	
Notes (inhalation LC₅₀)	No information available.
Skin corrosion/irritation	No information available.
Serious eye damage/irritation	No information available.
Respiratory sensitisation	No information available.
Skin sensitisation	No information available.
Carcinogenicity	
IARC carcinogenicity	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
Inhalation	May be harmful if inhaled. Spray/mists may cause respiratory tract irritation. Ingestion May be harmful if swallowed.
Skin contact	May be absorbed through the skin. May be harmful in contact with skin. May cause skin irritation.
Eye contact	May cause eye irritation.

SECTION 12: Ecological information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1 Toxicity

12.1. Toxicity

Acute toxicity - fish LC₅₀, 96 hours: > 1000 mg/l, Freshwater fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >500 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: ~ 1640 mg/l, Scenedesmus subspicatus

Ecological information on ingredients.

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

Acute toxicity - fish LC₀, 96 hours: 1000 mg/l, Marinewater fish)

Acute toxicity - aquatic invertebrates EC₅₀, 24 hours: 1000 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₀, 72 hours: 1640 mg/l, Scenedesmus subspicatus

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 10 mg/l, Daphnia magna



Timber Inspired, Quality Driven

J30 External Grade D4 polyurethane adhesive

Safety Data Sheet

2,2'DIMORPHOLINYLDIETHYL ETHER

Acute toxicity - fish	LC ₅₀ , 96 hours: 2150 mg/l,
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: > 100 mg/l, Daphnia magna
Acute toxicity - microorganisms	EC ₅₀ , 3 hours: > 1000 mg/l, Bacteria

12.2. Persistence and degradability

Persistence and degradability	The product is not readily biodegradable.
Stability (hydrolysis)	Reacts with water.
Biological oxygen demand	< 10 g O ₂ /g substance

12.3. Bioaccumulative potential

Bioaccumulative potential	The product does not contain any substances expected to be bioaccumulating.
Partition coefficient	Not available.
Ecological information on ingredients.	

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

Partition coefficient	log Pow: 4.51
------------------------------	---------------

12.4. Mobility in soil

Mobility	The product is non-volatile.
-----------------	------------------------------

Ecological information on ingredients.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
---	---

12.6. Other adverse effects

Other adverse effects	Not determined.
------------------------------	-----------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).
14.1. UN number	Not applicable.
14.2. UN proper shipping name	
14.3. Transport hazard class(es)	No transport warning sign required.
14.4. Packing group	Not applicable.
14.5. Environmental hazards	
Environmentally hazardous substance/marine pollutant	No.
14.6. Special precautions for user	Not applicable.
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code	



Timber Inspired, Quality Driven

J30 External Grade D4 polyurethane adhesive

Safety Data Sheet

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by	Compliance
Revision date	15/09/2020
Revision	20
Supersedes date	13/01/2020
SDS status	Approved.
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure
Store Between	Store Between 5°C - 25°C
Contains SVHC	NO

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.