

Metolux

Hardeners



Product Data Sheet

Application and Use

Paste containing 50% benzoyl peroxide with a special mixture of plasticizer that makes the product homogenous and guarantee greater safety in the storing and use of peroxide. A formula specially designed to avoid separation problems, it can also be coloured with long-lasting effect. Designed & supplied for use as a 2% mix hardener with Metolux Fillers.

Used as a catalyst for polymerization of unsaturated polyester resins, particularly fillers and putties.

Physical & Chemical Characteristics

Appearance: creamy paste
 Peroxide content: 49/51 % - almost odourless
 Oxygen active content: 3.2 - 3.3 %
 Humidity: about 15%

Handling and Storage

The product must be stored at a temperature not exceeding 25°C and must not come into contact with direct light. There must be no contact with heat sources, stabilizing accelerants, metallic soaps or driers, or with rust, copper or other metal compounds.

Sizes

Product
10g, 20g, 30g, 40g

Use by Date

24 Months from the Manufacture date (printed at the seal) Manufacture date is denoted as 5 digits - XX (year) XXX (day of the year)

The information and data given is based on our own experience, research and testing and is believed to be reliable and accurate. However, as Chemfix Products cannot know the varied uses to which its products may be applied, or the methods of application used, no warranty as to the fitness or suitability of its products is given or implied. It is the users responsibility to determine suitability of use. For further information please contact our Technical department.