

TIMBAFIL HARDENER

Page: 1

Compilation date: 12/03/2010

Revision date: 12/11/2013

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: TIMBAFIL HARDENER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Hardener Component for Wood Repair

1.3. Details of the supplier of the safety data sheet

Company name: Chemfix Products Limited

Mill Street East

Dewsbury

West Yorkshire

WF12 9BQ

United Kingdom

Tel: +44 (0)1924 453886

Fax: +44 (0)1924 458995

Email: sds@chemfix.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Aquatic Acute 1: H400; Org. Perox. EF: H242; Skin Sens. 1: H317

Most important adverse effects: Heating may cause a fire. May cause an allergic skin reaction. Causes serious eye

irritation. Very toxic to aquatic life.

2.2. Label elements

Label elements:

Hazard statements: H242: Heating may cause a fire.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H400: Very toxic to aquatic life.

Signal words: Warning

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

GHS09: Environmental







TIMBAFIL HARDENER

Precautionary statements: P264: Wash skin thoroughly after handling.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P370+378: In case of fire: Use suitable media to extinguish.

2.3. Other hazards

Other hazards: Not applicable.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DIBENZOYL PEROXIDE BPO - REACH registered number(s): 01-2119511472-50-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-327-6	-	-	Aquatic Acute 1: H400; Eye Irrit. 2: H319; Org. Perox. B: H241; Skin Sens.	40-50%
			1: H317	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Consult a doctor.Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Not applicable.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Carbon dioxide.

Water spray. Dry chemical powder. Alcohol resistant foam.

[cont...]

Page: 2

TIMBAFIL HARDENER

Page: 3

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside keep bystanders

upwind and away from danger point.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Pick up mechanically. Transfer to a closable, labelled salvage container for disposal by

an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Store away from heat.

Keep away from direct sunlight.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): Building and construction work (SU19).

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIBENZOYL PEROXIDE BPO

TIMBAFIL HARDENER

Page: 4

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3	-	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste Colour: White

Odour: Characteristic odour

Oxidising: Oxidising (by EC criteria)

Solubility in water: Insoluble

Relative density: 1.1

9.2. Other information

Other information: SADT = 50 C. The SADT (self accelerating decomposition temperature) is an

experimentally determined temperature at which the product, in its conventional

packaging will decompose in a selfaccelerating reaction.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Substance/product is oxidizing when dry.

10.4. Conditions to avoid

Conditions to avoid: Heat. Direct sunlight.

TIMBAFIL HARDENER

Page: 5

10.5. Incompatible materials

Materials to avoid: Amines. Acids. Alkali. Heavy metal compounds.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DIBENZOYL PEROXIDE BPO

ORL	RAT	LD50	5000	mg/kg
VAPOURS	RAT	LD50	24.3	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Not applicable.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

DIBENZOYL PEROXIDE BPO

ALGAE	72H ErC50	0.0711	mg/l
Daphnia magna	48H EC50	0.110	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	0.0602	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

TIMBAFIL HARDENER

Page: 6

12.4. Mobility in soil

Mobility: Insoluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Waste code number: 03 03 99

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3108

14.2. UN proper shipping name

Shipping name: ORGANIC PEROXIDE, TYPE E, SOLID

(DIBENZOYL PEROXIDE)

14.3. Transport hazard class(es)

Transport class: 5.2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D
Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

TIMBAFIL HARDENER

Page: 7

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H241: Heating may cause a fire or explosion.

H242: Heating may cause a fire.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H400: Very toxic to aquatic life.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.

ENVIRONMENTAL CARE: Please do not dispose of uncured material. If disposing

please mix any waste product to its cured state.